

DESIGN AND CONSTRUCTION OF THE HARLAN TUNNELS

Presenter Name John Stanton

Presenter Title Chief, Geology Section

Duty Location Nashville, TN


Date of Presentation August 3, 2010



US Army Corps of Engineers
BUILDING STRONG




Project Location



BUILDING STRONG®

The Problem




April 1977



BUILDING STRONG®

Why In Harlan?




The Recommended Plan

- Diversions
- Levees and floodwalls
- Pump stations and gravity outlets
- Non-structural



BUILDING STRONG®

The Project Layout



Aerial View Along Tunnel Alignment



ING STRONG®

Feasibility of Tunnels

Typical debris
load on bridge
after April
1977.




BUILDING STRONG®

Physical Model, Waterways Experiment Station - Flow Test




BUILDING STRONG®

Modeling the Intake With Debris.



BUILDING STRONG®


The Tunnels Relative to Human Size.



BUILDING STRONG®

Geology of the Project

★ **Approximate Location of Harlan**




Landsat View,
South of the
Project



BUILDING STRONG®

Geologic Cross-section



BUILDING STRONG®



Typical Section Exposed on Road Cut at Highway 421.

A good location for gathering strikes
and dips.



BUILDING STRONG®

The Exploration Program

Horizontal Hole
Drilling




BUILDING STRONG®

Single Shot Camera Borehole Survey System.



BUILDING STRONG®



Core Recovery From the Horizontal Drilling

70% recovered as 10 ft.
unbroken cores.



BUILDING STRONG®



Videotaping the Holes




BUILDING STRONG®

Polar Plot of Discontinuities

North


Different symbols for different data sources such as angle holes, televiewer, or surface mapping.



South


BUILDING STRONG®

Point Load Testing Apparatus




STRONG®

Typical Sample After Testing



BUILDING STRONG®

Point Load Test Data For Hole CH-1






Other Field Testing.



BUILDING STRONG®

Pull Break Tensile Test



Cross-hole Seismic Velocity Profiling



NG STRONG®

Why Do the Profiling?




Ripping can be cheaper but is it feasible?




STRONG®


Estimating Ripping Production Vs. Seismic Velocity of the Rock Mass




Direct Shear Test Averages



X-ray Diffraction Data



Unconfined Compressive Strength.



Rock Mass Classification System Analysis

RMR System (CSIR)

	High Value	Low Value
1. Rock U_c Strength (10,557 psi - 5,412 psi)	6	3
2. RQD Rating (95 - 100)	20	20
3. Joint Spacing (1 Ft. - 10 Ft.)	30	20
4. Joint Roughness (Very Rough - Slightly Rough)	25	20
5. Groundwater (Dry - Moist)	10	7
6. Adjustment for Joint Orientation (Bedding)	<u>-10</u>	<u>-10</u>
Rock Mass Rating	82	61
Rock Classification	Very Good	Good




Rock Mass Classification System Analysis

Q System (NGI)

		High Value	Low Value
1.	RQD Range From Borings	100	95
2.	J _n Joint # (Massive to One Joint Set)	2.0	0.5
3.	J _r Joint Roughness (Smooth to undulating)	4.0	3.0
4.	J _a Joint Alteration (Unaltered)	1.0	1.0
5.	J _w Joint Water (Dry to Minor Inflows)	1.0	1.0
6.	SRF Stress Reduction Factor (Low to Medium)	2.5	1.0
$Q = RQD/J_n * J_r / J_a * J_w / SRF$			
Maximum Q = 100/0.5 * 4/1 * 1/1 = 800 Extremely Good Quality Rock			
Minimum Q = 95/2 * 3/1 * 1/2.5 = 57 Very Good Quality Rock			



Boundary Element Analysis




BUILDING STRONG®

Tunneling Methods

- **Drill and blast** - most commonly used flexible. Disruptive to rock mass.
- **Tunnel boring machines** - For long tunnels most economical. Least flexible. Least disruptive to rock mass.
- **Road headers** - limited rock strength. Most flexible. Not disruptive to rock mass.




Tunnel Excavation Plan




Phase I Top Heading by Road Header.

Phase II Bench by drill and blast with wall trimming by Road Header.



Two Heavy Duty Machines




Production Comparison

Excluding Downtime

Paurat Vs. Dosco

Average Production (Bank Cy/Day)



BUILDING STRONG®


Downtime/repairs



BUILDING STRONG®


Production Comparison

Paurat Vs. Dosco




BUILDING STRONG®

Top Heading Excavation Paurat Vs. Dosco



BUILDING STRONG®

Road Headers at Work




BUILDING STRONG®

Blasting the Bench



BUILDING STRONG®

Tunnel Utility Layout



BUILDING STRONG®

Ventilation System Design Silicosis Is a Concern!

Air Requirements:

Diesel Engines:	900 H.P. total x 100 C.F.M./H.P.	=	90,000 C.F.M.
Personnel:	15 Men x 200 C.F.M./Man	=	<u>3,000 C.F.M.</u>
Total Required:			93,000 C.F.M.

System Used = 100,000 C.F.M. → Air Velocity in top heading = 200 FPM

Fan System

Jet Air Fan Model R-4200-B w/ 200 H.P., 1,800 RPM Motor



BUILDING STRONG®

At the Heading



BUILDING STRONG®

Scrubber



BUILDING STRONG®

Alignment With Lasers



Support of the Roof..... Rock Bolts



10' long 1" \varnothing steel bolts on 5 foot centers.



Support of the Roof..... Shotcrete.



4" minimum of steel fiber
reinforced shotcrete



BUILDING STRONG®

The Upstream Portal



The End



BUILDING STRONG®