

SOO LOCKS AUTOMATED INSTRUMENTATION

Jeff Rakes

Instrumentation Coordinator

USACE - Huntington District

August 3, 2011



®

US Army Corps of Engineers
BUILDING STRONG®

Presentation Overview

Background

Purpose of Instrumentation

Design Considerations

Areas of Concern (AOC)

Questions




BUILDING STRONG®

Background

- Four Existing Parallel Locks (U.S. Side) – One Canadian Lock
- Located at the St. Mary's Falls Canal on the St. Mary's River
 - **Sabin** (North Canal – 80'W x 1350'L x 23'D) – Inactive with Cofferdams
 - **Davis** (North Canal - 80'W x 1350'L x 23'D) - Rarely Utilized
 - **Poe** (South Canal – 110' W x 1200' L x 32' D) Only lock capable of passing 1000' Lakers, the Great Lake Fleets largest vessels
 - **MacArthur** (South Canal – 80'W x 800'L x 29.5' D) Active, passing smaller vessels
- Only passage between Lake Superior and the lower Great Lakes
- Locks an average of 10,000 ships annually
- Closed from January through March due to Ice
- Listed on National Register of Historic Places
- Elevated viewing stands for summer crowds



Critical Inland Navigation Passage Way




BUILDING STRONG®

Complex, High Profile Site





BUILDING STRONG®

Complex, High Profile Design



BUILDING STRONG®

Complex, High Profile Design




Complex Weather Conditions



BUILDING STRONG®

Complex Weather Conditions



Long Cold Winter Season

6 Months = Average Low $< 32^{\circ}$

3 Months = Average High $< 32^{\circ}$

Highest Summer Month $< 80^{\circ}$

Only a few days annually $> 90^{\circ}$

Locks closed from January through March due to ice on the river

One of Snowiest Locations in Michigan

Average 128" of Snow / Year

Average 34" of Rain / Year



BUILDING STRONG®

Presentation Overview

Background

Purpose of Instrumentation

Design Considerations

Areas of Concern (AOC)

Questions



BUILDING STRONG®

Purpose of Instrumentation

Risk Management

- Our main priorities are to effectively identify and manage the risk associated with construction in such a manner that we insure the safety of on-site personnel and maintain the integrity, stability and operability of the Soo Locks.
- **No other issues can supersede these priorities.**



Purpose of Instrumentation

Risk Management

Monitor Changing Site Conditions

(Construction Control)

- The system is designed so that all potential concerns can be monitored via the automated system.
- The system design also incorporates monitoring of all potential concerns via manual instrumentation for verification of automated instruments and redundancy.
- Mobotix Cameras for remote observation / validation of extreme readings.



Purpose of Instrumentation

Risk Management

Monitor Changing Site Conditions

Cofferdam Early Warning Capabilities

- Audible / visual alarming as well as individual notifications as a result of threshold exceedance.
- Webpage hosting for all automated instruments including long term instrument data graphs for trend evaluations.



BUILDING STRONG®

Purpose of Instrumentation

Risk Management

Monitor Changing Site Conditions

Cofferdam Early Warning Capabilities

Design Verification

- Affirm assumptions made during design were appropriate. Factors of safety, site conditions, etc.
- Portions of the system can be left in place for long term performance monitoring.



BUILDING STRONG®

Presentation Overview

Background

Purpose of Instrumentation

Design Considerations

Areas of Concern (AOC)

Questions



BUILDING STRONG®

Design Considerations

Automated Data Acquisition System (ADAS)

- Adequate configurability and expandability.
- Compatibility with various types of sensors to be utilized.
- Ability to withstand anticipated vibrations.
- Flexible and resilient communications system.
- Low power operation.
- Rugged construction / ability to perform in extreme cold weather conditions.
- Proven record of reliable performance in similar construction monitoring installations.



Design Considerations

Automated System Types Evaluated

- Real Time System

- (Supervisory Control and Data Acquisition – SCADA)

- Network of rugged remote computers monitoring numerous sensors of various types.
 - Easy to network with **higher bandwidth and power requirements.**
 - Threshold exceedance alarming capability.
 - Will continue to collect and evaluate data even if communications with CMU have stopped. Remote programming capability.
 - Real time monitoring. Most commonly used to acquire large numbers of sensor readings very quickly. 100 data value sets per second.
 - Typically utilized for fast response, equipment control applications.
 - **Not as suitable for long term, unattended application w/potential high hazard failure due to higher bandwidth / power requirements.**



Design Considerations

Automated System Types Evaluated

- **Distributed Intelligence Logger**
 - Network of rugged remote computers monitoring numerous sensors of various types.
 - Easy to network with **low bandwidth and power requirements.**
 - Threshold exceedance alarming capability.
 - Will continue to collect and evaluate data even if communications with CMU have stopped. Remote programming capability.
 - Near real time monitoring but not as fast as SCADA. One data value set per second.
 - Suitable for outdoor applications in harsh environments.
 - **Suitable for long term, unattended application w/potential high hazard failure.**



Design Considerations



Automated System Type Selected

- **Distributed Intelligence Logger**
(Campbell Scientific CR1000 Dataloggers)
 - Recognized as industry standard datalogger for Geotechnical / Structural monitoring.
 - Long successful record of use in similar monitoring applications.
 - Field proven interface module for automated readings from Vibrating Wire Instruments (AVW200 & AVW206).
 - Field proven interface module for automated readings from MTDR Cables (TDR100).
 - Wide range of communication options.
 - Local and remote monitoring units (LMU & RMU).
 - Communicate with hardwired and wireless remote multiplexers (RMX & RIO).



Design Considerations


CR1000 Remote Monitoring Unit (RMU)




BUILDING STRONG®

Design Considerations

Wired (RMX) and Wireless (RIO) Multiplexers



REMOTE MULTIPLEXER ENCLOSURE MOUNT (RMX) INSTALLATION DETAILS






PIEZOMETER WELL LOCATION WITH RIO ENCLOSURE MOUNT AND SOLAR PANEL DETAILS



BUILDING STRONG®

Design Considerations Instruments



BUILDING STRONG®

Design Considerations

Instrument Types Selected

- Inclinometers (In-Place & Manual)
Overturning, Sliding & Deformation
- Metallic Time Domain Reflectometry Cables (MTDR)
Overturning, Sliding & Deformation
- Tiltmeters Overturning
- Load Cells Tieback Loading
- Piezometers (Vibrating Wire & Casagrande) Seepage
- Crackmeters (Manual) Crack Formation, Vibration
- Alignment and Settlement Pins / Saw Cuts Settlement, Rebound, Deflection, Overturning & Sliding



Design Considerations

Instrument Types Considered But Excluded

- Optical Time Domain Reflectometry Cables (OTDR)
 - Readout equipment and fiber optic cable are cost prohibitive.
- Shape AccelArrays (SAA)
 - Relatively new instrument type lacking long term record of field performance. Cost prohibitive.
- Terrestrial Position System (TPS)
 - Reduced capability during long winter season due to ice / snow buildup on prisms. Line of site required.
- Global Positioning System (GPS)
 - Antennas susceptible to ice / snow buildup.
 - Cost prohibitive.




Design Considerations Instrument Summary

Instruments

IPI	282
Inclinometer	19
MTDR	49
Tilt Meter	52
Load Cell	76
VW Piezo	83
Pool Trans	4
A&SP	608
Saw Cut	184
Mobotix	6

550 Automated
800 Manual



Presentation Overview

Background

Purpose of Instrumentation

Design Considerations

Areas of Concern (AOC)

Questions



BUILDING STRONG®


Areas of Concern (AOC)

Seven Areas Of Concern Identified

- AOC 1 – North Sabin Chamber Monoliths
- AOC 2 – North Sabin Wide Wall and South Sabin Chamber and Wide Wall Monoliths
- AOC 3 – Cofferdam Cells
- AOC 4 – Cutoff Walls
- AOC 5 – North Davis Chamber Monoliths
- AOC 6 – South Davis Chamber Monoliths
- AOC 7 – Historic Davis, Administration Building / Service Tunnel



AOC1 – North Sabin Chamber Monoliths




AOC1 – North Sabin Chamber Monoliths

Construction Concerns

- Overturning (Dewatering / reface and chamber deepening)
 - IPI (19), Inclinometers (10), MTDR (28), Uniaxial Tilt Meters (19), Survey Points (117), Saw Cuts (39)
- Seepage (North groundwater through exposed rock)
 - Piezometers (23)
- Settlement / Rebound (Construction activities)
 - Survey Points (117)
- Sliding (Dewatering / construction activities / chamber deepening)
 - IPI (19), Inclinometers (10), MTDR (28), Tilt Meters (19), Survey Points (117), Saw Cuts (39)
- Tieback Loading (Anchors)
 - Load Cells (76)



AOC2 – N Sabin Wide Wall and S Sabin Chamber & Wide Wall Monoliths




AOC2 – N Sabin Wide Wall & S Sabin Monoliths

Construction Concerns

- Overturning (Dewatering)
 - Biaxial Tilt Meters (29), Survey Points (159), Saw Cuts (53)
- Seepage (North groundwater and pansey bed)
 - Piezometers (23)
- Settlement / Rebound (Construction activities)
 - Survey Points (159)
- Sliding (Dewatering / construction activities)
 - Tilt Meters (29), Survey Points (159), Saw Cuts (53)



AOC3 – Cofferdam Cells



BUILDING STRONG®


AOC3 – Cofferdam Cells

Construction Concerns

- Overturning (Dewatering)
 - IPI (7), Inclinometers (7), Survey Points (56)
- Seepage (Upper and lower pools)
 - Piezometers (16)
- Sliding (Dewatering)
 - IPI (7), Inclinometers (7), Survey Points (56)



AOC4 – Cutoff Walls



BUILDING STRONG®


AOC4 – Cutoff Walls

Construction Concerns

- Deformation (Construction Activities)
 - IPI (16), MTDR (16), Biaxial Tilt Meters (4)
- Seepage (Upper and lower pools)
 - Piezometers (24)



AOC5 – North Davis Chamber Monoliths




AOC5 – North Davis Chamber Monoliths

Construction Concerns

- Overturning (Dewatering / Pansey bed excavation / Davis backfill)
 - IPI (3), MTDR (3), Survey Points (138), Saw Cuts (46)
- Seepage (Upper and lower pools)
 - Piezometers (3)
- Deflection (Davis backfill)
 - IPI (3), MTDR (3), Survey Points (138), Saw Cuts (46)
- Sliding (Dewatering / Pansey bed excavation / Davis backfill)
 - IPI (3), MTDR (3), Survey Points (138), Saw Cuts (46)



AOC6 – South Davis Chamber Monoliths




AOC6 – South Davis Chamber Monoliths

Construction Concerns

- Overturning (Dewatering / Construction activities)
 - IPI (2), Inclinometers (2), MTDR (2), Survey Points (138),
Saw Cuts (46)
- Seepage (Poe Lock)
 - Piezometers (7)
- Deflection (Dewatering / Construction activities / Davis backfill)
 - IPI (2), Inclinometers (2), MTDR (2), Survey Points (138),
Saw Cuts (46)
- Sliding (Dewatering / Construction activities)
 - IPI (2), Inclinometers (2), MTDR (2), Survey Points (138),
Saw Cuts (46)



AOC7 – Historic Davis Building, Administration Building / Service Tunnel



BUILDING STRONG®

AOC7 – Historic Davis Building, Administration Building / Service Tunnel

Construction Concerns

- Crack Formation (Blasting / Construction activities)
 - Pre Construction Surveys / Avongard Crack Meters
VW Crack Meters if necessary
- Vibration (Blasting / Construction activities)
 - Pre Construction Surveys / Avongard Crack Meters
VW Crack Meters if necessary



QUESTIONS



Jeff Rakes
Ronald.J.Rakes@USACE.Army.Mil
CELRH Instrumentation Coordinator
Dam and Levee Safety Section
304-399-5809



BUILDING STRONG®