

# Emergency Response to Rockfall on Tennessee's Interstate 75

Presentation By: J. Reid Bailey, PE  
GeoStabilization International  
[reid@gsi.us](mailto:reid@gsi.us)

Martin J. Woodard, PhD PG PE  
GeoStabilization International  
[marty@gsi.us](mailto:marty@gsi.us)

Bob Lyne,  
GeoBrugg  
[Bob.Lyne@geobrugg.com](mailto:Bob.Lyne@geobrugg.com)



# I-75 MP 142.5 prior to February 26, 2016



# Failure onto I-75





# Geology

- Coal Bearing Region
  - Hance Formation
  - Interbedded **shale**, sandstone, siltstone, **underclay**, coal
  - Strong Units
    - Sandstones
    - Limestones
  - Weak Units
    - Shale, underclay



# Geologic Structure Control vs. Differential Weathering Control




# Geologic Structure in Appalachian Coal Region

- Discontinuities
  - Geologic Breaks in the rock
- Bedding Plane (generally horizontal)
- Tectonic Joints
- Valley Stress Relief Joint





# Tectonic Joints



Tectonic Joints are compressional joints; just like a compression test in concrete.



# Tectonic Joints in Coal Region



Compression caused by plates colliding, compression lateral  
Creates "Saw-tooth" appearance





# Valley Stress Relief Joints

- Overburden Rock is removed
- Stress is Relieved
- Relaxation of the the rock mass causes joints
- Characterized as
  - Nearly vertical
  - Continuous throughout slope
  - Parallel to valley (commonly rivers)




# Local Failures with Valley Stress Relief Joints



Less durable units can erode quicker than more durable units creating overhangs. As erosion continues towards the VSRJ rockfalls can occur



# Large Failures Caused By Valley Stress Relief Joints (VSRJ)



Some slopes can fail along the VSRJ if undercutting or pressures are high enough



# I-75 Failure



Vertical Fractures  
(Related to Valley Stress  
Relief Joints)


Seep Zones

Weak Zones such as a  
claystone or underclay




# Emergency Response Requirements

- Repair the slope working in conjunction with TDOT and Blalock
- Open Southbound lanes to traffic within 7 days
- Open Northbound lanes to traffic within 21 days



# Construction Plan

- Above Failure
  - Lay back to a 1H: 1V
  - Pinned Mesh System
- Near Failure Plane
  - Develop a mid-slope Bench
- Below failure plane
  - Approximate 3H: 1V
  - Need to move fast with road opening requirements






# Blasting

(attempt to make things faster)


- Have to blast upper section to 1H: 1V Slope
- Remove high hazard to southbound lanes to open up lanes
- Remove failed material to prepare to stabilize
- Attempt to do all in ONE step





# Results of Blasting

- Top section 1H: 1V slope developed
- Rocks falling only onto Northbound Lanes
- Safe to open Southbound lanes to traffic in less than 1 week



# Excavation Coordination with Blalock Construction



# Excavation of Failed material after blasting

- During excavation vertical structure noticed in middle of slope
- All failed material in front
- Can't continue 1H: 1V slope
- Valley Stress Relief Joint



# Excavation and Preparation of Vertical Feature



# Slope Protection

- Left with a vertical feature with a 1H:1V Slope above
- GeoBrugg Tecco G65 3mm - Pinned Mesh on 1H:1V Slope above
- Vertical Cut - Shotcrete Surface Protection – VSRJ Area



# The TECCO<sup>®</sup> System

1. High-tensile steel wire TECCO<sup>®</sup> meshes




2. TECCO<sup>®</sup> system spike plates



3. Anchors




4. RUVOLUM Dimensioning Concept







Cross section A-A



General nail arrangement



Detail A



TECCO® mesh connection vertical normally without overlap



Connection clip T3 (1 Clip per mesh)

TECCO® System spike plate P33



TECCO® System spike plate P66



Connection clip T3



Press claw Typ 2




modification:	M:%	substitute for: GE-1003e ed. 18.04.12
		replaced by:
<b>TECCO® G65/3</b> System drawing		drawn 06.01.14 hb
		checked 06.01.14 hb
		approved 06.01.14 R
GEOBRUGG AG		<b>GEOBRUGG</b>
		<b>GE-1003e</b>

This document is proprietary to Geobrugg AG and is copyrighted with all rights reserved. It may not in whole or in part, be distributed, copied in any form, translated or otherwise reproduced in any form.

This document will not be exchanged when being modified

# Cost Optimization



# Staging Work

- Working on Upper pinned mesh slope area
- Working on VSRJ area
- Required to stage work so one worker isn't working directly below another worker



# Staging Work



# Working in Stages



# Night Work



# Pinned Mesh Area (top of slope)



# Pinned Mesh/Shotcrete Area









Thank You

